

SPRING 제원표

단위: 압력(Kg/cm²) 길이(mm)

N/O	모 델	Spring N/O	압력범위	색상	길이	두께	내경	비고	
1	H/O Pilot 1차	70017P036	0.015 - 0.04	천연색	38	1.3	19		
	H/O Pilot 2차	70017P075	0.035 - 0.071	Light Blue	40	1.6	19.8		
		70017P078	0.14 - 0.4	Yellow / Orange	45	2.7	19.5		
		70017P079	0.2 - 0.55	Green / Orange	44	2.9	19.1		
		70017P079	0.4 - 1.0	Green / Orange	44	2.9	19.1	Reducing 부착	
		518250			32	1.25	16.5	Blance용	
	518236			19.4	0.45	6			
2	ZSC & Z138	71411P010	0.07 - 0.35	Green	55	1.7	16.3		
		71411P043	0.14 - 0.7	Brown / Blue	50	2	16.9		
		71411P011	0.21 - 2.1	Yellow	53.3	2.4	15.5		
		71411P012	0.7 - 5.3	Red	50.7	3.4	15.7		
		71411P014	1.76 - 10.5	Blue	53.8	4.1	15.3		
		71411P009	7 - 15.8	White	51	4.6	16.5		
		71411P046	14 - 22.8	White / Red					
		71411P008	10.5 - 42.2	Gold					
		70157P004	표준 Blance Spring						
		70782P001	Blance Spring 대응 Nutdia stem						
3	1203Pilot	70017P001	0.013 - 0.023	Green	70.4	1.3	19.6		
		70017P002	0.023 - 0.038	Blilk / Orange					
		70017P073	0.035 - 0.14	Blilk					
		70017P078	0.14 - 0.42	Yellow / Orange	45	2.7	19.5		
4	1800B2 REG'	70017P043	0.0089- 0.0152	Blue	90	1.4	20		
		70017P044	0.014 - 0.216	Yellow					
		70017P042	0.015 - 0.038	Green	85	1.8	19.9		
		70017P060	0.03 - 0.07	White	76.4	2.5	19.5		
		70017P049	0.61 - 0.142	Red	95.1	2.5	19.9		
	1800B2 Opso	71403P005	0.035 - 0.088	Green	43	1	9.8		
		71403P004	0.07 - 0.21	Black	42	1.3	9.8		
	1800B2 Relief	71403P013	설정압력 + 140 ~ 220						

단위: 압력(Kg/cm²) 길이(mm)

N/O	모 델	Spring N/O	압력범위	색상	길이	두께	내경	비고
5	2000 REG'	71411P020	0.035 - 0.07	Brown / white	210	4.5	52	
		71411P021	0.07 - 0.18	White	206	6.2	51.8	
		71411P022	0.18 - 0.35	Orange / Balck	184	7.8	51.3	
		71411P023	0.35 - 0.7	Black	178	9.2	52.5	
		71411P024	0.7 - 1.0	Yellow / Green	172	10.2	51.4	
6	1800 REG'	71424P017	0.009 - 0.0015	Red	160	2.7	40.5	
		71424P018	0.013 - 0.02	Orange	185	2.6	40	
		71424P019	0.021 - 0.035	Yellow	181	3.4	40	
		71424P020	0.036 - 0.071	Green	195	3.8	39.3	
		71424P021	0.07 - 0.14	Blue	194	4.9	36.6	
		71424P022	0.14 - 0.21	Brown / Green	188	5.3	36.9	
		71424P023	0.21 - 0.35	Black / Green	160	6	33.6	
	71424P027	0.35 - 0.45	Red / Green	159	7.7	34.2		
1800 REG'	70017P077	설정압력 + 80 ~ 220 Green색						Relief
	70017P078	설정압력 + 100 ~ 500 Black / Orange색						
		70017P036	0.015 - 0.035		37.4	1.35	18.9	
		70017P075	0.035 - 0.071	Light Blue	40	1.6	19.8	
		70017P076	0.07 - 0.14	Red	40.3	2	19.5	

7	1800, 2000 REG SSV, OPSO	70017P077	0.14 - 0.21	Green	47.3	2.2	19.4	
		70017P078	0.21 - 0.35	Orange / Yellow	45	2.7	19.5	
		70017P079	0.35 - 0.56	Orange / Green	44	2.9	19.1	
		70017P078	0.56 - 0.98	Orange / Yellow	45	2.7	19.5	Reducing
		70017P079	0.98 - 1.4	Orange / Green	44	2.9	19.1	
8	HPR 10, 15	71421P009	0.18 - 0.35	Red / Black	156	4.2	35	
		71421P011	0.35 - 1.05	Green / Black	151	6.2	35.8	
		71421P012	1.05 - 1.8	Yellow	157	6.2	35.8	
9	HPR 30, 35	71421P011	1.7 - 5.2	Green / Black	151	6.2	35.8	
		71421P013	5.2 - 8.8		152	6.35	35.3	
10	10 L	70017P071	0.025 - 0.075	Black	40	2	19.5	
		70017P072	0.05 - 0.1					
		70017P077	0.1 - 0.18	Green	47.3	2.2	19.4	
		70017P078	0.18 - 0.25	Orange / Yellow	45	2.7	19.5	
		70017P079	0.2 - 0.5	Orange / Green	44	2.9	19.1	
11	J - 48KH	J4806 - 76	0.07 - 0.21	Green / Gold				
		J4806 - 63	0.21 - 0.35	Grey				
		J4806 - 78	0.35 - 0.76	Green / Pink	122	3.85	28.8	
12	J - 48KL 1"	J4808 - 004	0.012 - 0.024	Red /Yellow				
		J4808 - 011	0.023 - 0.037	Red /Silver	89	1.7	39.1	
		J4808 - 007	0.037 - 0.062	Red /Black	89.8	2.4	34.2	
		J4808 - 004	0.062 - 0.102	Blue /Black	83.7	2.9	34.3	
		J4808 - 005	0.102 - 0.15	Blue /Orange				
13	J - 48KL 2"	J4809K - 006	0.012 - 0.024	Silver / Yellow				
		J4809K - 007	0.023 - 0.037	Silver / Gold				
		J4809K - 008	0.037 - 0.062	Silver / Green				
		J4809K - 005	0.062 - 0.15	Silver / Green				
14	V - 51	125660	0.18 - 0.4	Black / White	102	4.5	38	외경
		155490	0.34 - 0.8	Alamin / Black	130	5	37	외경
15	BM - 6	17360	0.025 - 0.045	Black / white	75	1.8	30	OS/66-BP
		174390	0.2 - 0.6		75	2.5	30	OS/66-MP
		197080	3.0 - 7.0		75	5	30	OS/66-APA